


Product		Dimensions	Notes
1U Blanking Panel Item No. 10031 (Black) or 10114 (White)		19" x 1.75" (482.5 x 44.45mm) 1U Sealing size	Cantilevered sealing vanes eliminate the gap between adjoining Blanking Panels or with installed equipment.
2U Blanking Panel Item No. 10033 (Black) or 10115 (White)		19" x 3.5" (482.5 x 89mm) 2U Sealing size	Tool-free, snap-in installation requires no additional parts or components for installation
1U Blanking Panel with Temperature Strip Item No. 10035		19" x 1.75" (482.5 x 44.45mm) 1U Sealing size	Color-coded temperature ranges indicates potential hot spots by color based on ASHRAE Standard
2U Blanking Panel with Temperature Strip Item No. 10038		19" x 3.5" (482.5 x 89mm) 2U Sealing size	Easy-pull removal for any EIA-310-E standard openings using ergonomically designed finger grips
1U Pass Through Blanking Panel Item No. 10112		19" x 1.75" (482.5 x 44.45mm) 1U Sealing size	Provides additional rack sealing where cables prevent solid blanking panels from being installed.
2U Pass Through Blanking Panel Item No. 10113		19" x 3.5" (482.5 x 89mm) 2U Sealing size	Provides an effective airflow sealing solution when used in conjunction with pullout KVM switches.
Upsite® Temperature Strip Item No. 10009		10" x 1" (254 x 25.4mm)	Calibrated in accordance with the American Society for Testing and Materials (ASTM) Standard E 1061-94 using equipment
Round 4" Rack Mount Grommet Item No. 40002		4"(102mm) Diameter Maximum Cutout Size Sealed	Split feature of the HotLok Round Rack Mount Grommet allows product installation or removal without disturbing cables